

TABLE 1

Horizontal bend for DI-K7 pipe										
Pipe dia (mm)	Pipe OD (mm)	Angle (degrees)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	H (mm)
150	170	11.25	250	125	1000	556	444	470	150	150
		22.5	400	200	1000	556	444	470	150	150
		45	650	325	750	417	333	520	175	175
300	326	11.25	450	225	1000	556	444	626	150	150
		22.5	900	450	1000	556	444	626	150	150
		45	1500	600	1300	743	557	676	175	175
350	378	11.25	650	325	1000	556	444	678	150	150
		22.5	1200	500	1500	853	647	678	150	150
		45	2050	600	1600	946	654	778	200	200
400	429	11.25	800	300	1000	576	424	729	150	150
		22.5	1550	700	1150	647	503	729	150	150
		45	2650	800	1300	766	534	829	200	200
150	170	11.25	300	150	1000	556	444	470	150	150
		22.5	550	250	1000	563	437	470	150	150
		45	1000	500	850	472	378	520	175	175
200	222	11.25	500	250	1000	583	467	522	150	150
		22.5	650	325	1200	667	533	522	150	150
		45	1250	650	1200	663	537	522	150	150
63	63	11.25	300	200	1000	533	467	363	150	150
		22.5	600	400	1000	533	467	363	150	150
		45	700	450	1000	536	464	363	150	150
75	75	11.25	300	200	1000	533	467	375	150	150
		22.5	500	350	1000	529	471	375	150	150
		45	800	500	1000	538	462	375	150	150
90	90	11.25	300	225	1000	524	476	390	150	150
		22.5	500	350	1000	529	471	390	150	150
		45	800	500	1000	538	462	390	150	150
110	110	11.25	300	200	1000	533	467	410	150	150
		22.5	500	350	1000	529	471	410	150	150
		45	700	350	1000	556	444	410	150	150
125	125	11.25	400	300	1000	524	476	425	150	150
		22.5	700	350	1200	667	533	425	150	150
		45	700	350	1150	639	511	425	150	150
63	63	11.25	300	200	1000	533	467	363	150	150
		22.5	600	400	1000	533	467	363	150	150
		45	700	450	1000	536	464	363	150	150
75	75	11.25	300	200	1000	533	467	375	150	150
		22.5	500	350	1000	529	471	375	150	150
		45	750	425	1000	546	454	375	150	150
90	90	11.25	300	200	1000	533	467	390	150	150
		22.5	500	350	1000	529	471	390	150	150
		45	700	350	1000	556	444	390	150	150
110	110	11.25	300	200	1000	533	467	410	150	150
		22.5	600	400	1000	533	467	425	150	150
		45	650	325	1000	556	444	425	150	150
140	140	11.25	300	200	1000	533	467	440	150	150
		22.5	600	400	1000	533	467	440	150	150
		45	650	300	1000	561	439	440	150	150
63	63	11.25	300	200	1000	533	467	363	150	150
		22.5	600	400	1000	533	467	363	150	150
		45	700	350	1000	556	444	363	150	150
75	75	11.25	300	200	1000	533	467	375	150	150
		22.5	550	350	1000	537	463	375	150	150
		45	700	350	1000	556	444	375	150	150
90	90	11.25	300	200	1000	533	467	390	150	150
		22.5	500	325	1000	535	465	390	150	150
		45	700	350	1000	556	444	390	150	150
110	110	11.25	300	200	1000	533	467	410	150	150
		22.5	500	275	1000	548	452	410	150	150
		45	700	300	1000	567	433	410	150	150
125	125	11.25	300	200	1000	533	467	425	150	150
		22.5	500	275	1000	548	452	425	150	150
		45	700	300	1000	567	433	425	150	150
140	140	11.25	300	200	1000	533	467	440	150	150
		22.5	600	350	1000	544	456	440	150	150
		45	550	250	1000	563	437	440	150	150
63	63	11.25	300	200	1000	533	467	363	150	150
		22.5	600	400	1000	533	467	363	150	150
		45	800	450	1000	560	440	363	150	150

TABLE 2

Vertical upturn bend for DI-K7 pipe					
Pipe dia (mm)	Pipe OD (mm)	Angle (degrees)	A (mm)	B (mm)	E (mm)
150	170	11.25	1000	500	470
		22.5	1000	500	470
		45	1000	500	470
300	326	11.25	1000	650	626
		22.5	1000	650	626
		45	1000	650	626
350	378	11.25	1000	700	678
		22.5	1000	700	678
		45	1150	750	678
400	429	11.25	1000	750	729
		22.5	1000	750	729
		45	1400	800	729
150	170	11.25	1000	500	470
		22.5	1000	500	470
		45	1000	500	470
200	222	11.25	1000	550	522
		22.5	1000	550	522
		45	1000	550	522
63	63	11.25	1000	400	363
		22.5	1000	400	363
		45	1000	400	363
75	75	11.25	1000	400	375
		22.5	1000	400	375
		45	1000	400	375
90	90	11.25	1000	400	375
		22.5	1000	400	375
		45	1000	400	375
110	110	11.25	1000	450	410
		22.5	1000	450	410
		45	1000	450	410
125	125	11.25	1000	450	425
		22.5	1000	450	425
		45	1000	450	425
63	63	11.25	1000	400	363
		22.5	1000	400	363
		45	1000	400	363
75	75	11.25	1000	400	375
		22.5	1000	400	375
		45	1000	400	375
90	90	11.25	1000	400	375
		22.5	1000	400	375
		45	1000	400	375
110	110	11.25	1000	450	410
		22.5	1000	450	410
		45	1000	450	410
125	125	11.25	1000	450	425
		22.5	1000	450	425
		45	1000	450	425
63	63	11.25	1000	400	363
		22.5	1000	400	363
		45	1000	400	363
75	75	11.25	1000	400	375
		22.5	1000	400	375
		45	1000	400	375
90	90	11.25	1000	400	375
		22.5	1000	400	375
		45	1000	400	375
110	110	11.25	1000	450	410
		22.5	1000	450	410
		45	1000	450	410
125	125	11.25	1000	450	425
		22.5	1000	450	425
		45	1000	450	425
63	63	11.25	1000	400	363
		22.5	1000	400	363
		45	1000	400	363
75	75	11.25	1000	400	375
		22.5	1000	400	375
		45	1000	400	375
90	90	11.25	1000	400	375
		22.5	1000	400	375
		45	1000	400	375
110	110	11.25	1000	450	410
		22.5	1000	450	410
		45	1000	450	410
125	125	11.25	1000	450	425
		22.5	1000	450	425
		45	1000	450	425
63	63	11.25	1000	400	363
		22.5	1000	400	363
		45	1000	400	363
75	75	11.25	1000	400	375
		22.5	1000	400	375
		45	1000	400	375
90	90	11.25	1000	400	375
		22.5	1000	400	375
		45	1000	400	375
110	110	11.25	1000	450	410
		22.5	1000	450	410
		45	1000	450	410
125	125	11.25	1000	450	425
		22.5	1000	450	425
		45	1000	450	425
63	63	11.25	1000	400	363
		22.5	1000	400	363
		45	1000	400	363
75	75	11.25	1000	400	375
		22.5	1000	400	375
		45	1000	400	375